

GC6492-1ST-OF-SA-P

Cylinder bed variable top differential feed lockstitch sewing machine

With machine head oil-free, touching panel, sleeve attaching device




Product features

- Set the whole machine main servo system and auxiliary differential programming system as one.
- The stepper motor shaft is directly connected to the differential parts, to complete the action of changing the differential.
- Suitable for different fabrics, such as general fabric, non-ironing fabric, chiffon, velvet fabric etc.
- Computer control the number of segments and capacity, effectively improve production efficiency.
- Use servo motor controls the capacity of each section, one upper sleeve arc can be set up to 9 sections, to meet all the requirements of the sleeve process.
- Machine head is completely oil-free (no white oil, but imported high temperature resistant solid grease lubrication).

Function and configuration




Can be set up to 9 sections differential mode



Sleeve attaching device



Extension roller stand (optional)



Machine head is oil-free, all above parts adopt micro-oil technology

Scope of application



Suitable for down jacket, suit, woolen coat, casual wear, trench coat, tang suit and other sleeves.

Technical parameter

○ Optional — None

GC6492-1ST-OF-SA-P	DB*1 7-18#	0-4mm	★	★	★	★	5-13	Forward≥3:1 Reverse≤0.5:1	31.8mm
The height of feeding fabric	The lifting height of feed presser foot	The light height of upper feed dog	Machine head oil-free	Sealed oil tank	Bottom differential electronic adjustment				
8mm	2.5-5mm	3-5mm	○	—	—	4000	650x245x550	50/48	